

# Environmental Product Declaration

In accordance with ISO 14025 and EN 15804:2012+A2:2019

## ODE ISIPAN XPS STD Insulation Materials

**Programme:**

The International EPD® System  
[www.environdec.com](http://www.environdec.com)

**Programme Operator:**

EPD Turkey, fully aligned  
with International EPD System

**S-P Code:**

S-P-03943

**Publication Date:**

16.06.2021

**Validity Date:**

15.05.2026

**Geographical Scope:**

Global



An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com)

# Programme Information

Programme	The International EPD® System	EPD Turkey, managed and run by:
	EPD International AB Box 210 60 SE-100 31 Stockholm, Sweden	SÜRATAM, <a href="http://www.suratam.org">www.suratam.org</a> Nef 09 B Blok No:7/15 34415 Kağıthane/Istanbul, Turkey
	<a href="http://www.environdec.com">www.environdec.com</a> <a href="mailto:info@environdec.com">info@environdec.com</a>	<a href="http://www.epdturkey.org">www.epdturkey.org</a> <a href="mailto:info@epdturkey.org">info@epdturkey.org</a>
Product Category Rules (PCR):	2019:14 Version 1.11, 2021-02-05, Construction Products and CPC 54 Construction Services, EN 15804:2012 + A2:2019 Sustainability of Construction Works	
Independent third-party verification of the declaration and data, according to ISO 14025:2006:	EPD process certification EPD verification <b>X</b>	
Third party verifier:	Professor Vladimír Kocí	
Approved by:	The International EPD® System	
Procedure for follow-up of data during EPD validity involves third party verifier: NO		

The EPD owner has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804.



# About ODE

ODE embarked on its business journey in 1985 with contracting operations. In 1998, ODE decided to move forward in the insulation industry, one that would serve Turkey's need. Having become an importer in 1990 and a manufacturer in 1996, ODE now manufactures products in 2 main categories, Building and HVAC insulation. ODE is now among the largest manufacturers of the insulation industry with 5 state-of-the-art manufacturing facilities, over 4 thousand product varieties, and expert workforce.

We manufacture extruded polystyrene thermal insulating material under the brand of ODE Isıpan; polymer modified bituminous waterproofing blankets under the brand of ODE Membrane, glass wool products used for heat and sound insulation and fire safety under the brand of ODE Starflex; and elastomeric rubber foam insulating material under the brand of ODE R-Flex.

As its Eskişehir Manufacturing Facility comes into play, ODE which currently exports to 5 continents aims to increase its export capacity even further, and become the leader in waterproofing in Turkey.

ODE reflects its social responsibility awareness to all its operations, and is the first company in the insulation industry of Turkey to publish a "Corporate Social Responsibility Report". Furthermore, ODE has been the first among its peers to earn the internationally recognized Environmental Product Declaration (EPD) certificate which is compatible with European standards and which applies for all markets to all heat and water insulation products manufactured by ODE in its facilities in Çorlu.

Having implemented pioneering efforts toward raising public awareness of insulation and energy awareness, and taking care to be involved in projects that will hand down permanent value to the future, ODE changed its company motto to "Insulates the Future" in 2014. In knowledge of the universal responsibility of being in the global market, ODE continues to operate as a company which encourages its social stakeholders through visionary and innovative work.



*ODE Çorlu/Tekirdağ, Turkey  
Production Facilities*



*ODE Eskişehir, Turkey  
Production Facilities*

# About Product

ODE Isipan is manufactured in two groups, PRM (Premium) and STD (Standard), and with various compressive strengths and thermal conductivity specifications.

The available types are: ODE Isipan DT (smooth) for thermal insulation of floors and roofs, ODE Isipan MD (corrugated) for thermal insulation of walls, columns, and beams, ODE Isipan BD (checkered) for thermal insulation of walls, columns, and beams.

The surfaces of MD (corrugated) and BD (checkered) products have high level of adhesion with plaster and adhesive. Both surfaces of DT products are smooth and reinforced.

- ODE Isipan is manufactured in the  $\lambda = 0.035-0.038$  W/ (m.K) thermal conductivity range in accordance with the EN 131642 standard.
- Thanks to its high compressive and bending strength, it does not suffer loss of thickness with time.
- Can be cut with any type of cutting tool, does not crumble or cause wastage.
- Has a Closed Cell Structure.
- ODE Isipan, has optimum water diffusion resistance factor  $\mu=100$  which prevents condensation while allowing the product to breath and is classified as WL (0.7) TS according to EN11364.
- It can be used without compromising its properties between  $-50^{\circ}\text{C}$  and  $+250^{\circ}\text{C}$ .

The weights providing  $1 \text{ m}^2\text{K/W}$  thermal insulation for ODE ISIPAN STD XPS insulation materials is 0.89 kg.



For product accessories, certificates and detailed information, please click or scan the QR code

# Technical Specifications

	STANDARD	UNIT	Value
Thickness	EN 823	mm	20-80
	Tolerance T1		± 3
Compressive Strength (10% relative deformation)	EN 826	kPa	100-200
Thermal Conductivity - $\lambda$	EN 12667	W/m*K	0.035-0,038
Resistance - R		m <sup>2</sup> *K/W	≥ 0.85-2.00
Width	EN 822	mm	600 ± 8
Length	EN 822	mm	1200 ± 8
Deviation From Squareness	EN 824	mm/m	± 5
Fire Response	EN ISO 11925-2	Euro Class	E
Deformation Under Specific Compressive Strength and Temperature Conditions	EN 1605	%	≤ % 5, DLT(1)5
Long-Term Water Absorption by Full Immersion	EN 12087	%	≤ % 0.7, WL(T)0.7
Water Vapor Diffusion Resistance Factor	EN 12086	μ	100
Number of Boards in Package	-	-	6-14

## APPLICATION AREA

ODE ISIPAN is used for the thermal insulation of floors and roofs, walls, columns, and beams. ODE ISIPAN STD has a thermal conductivity in the range of 0.35-0.38 W(m.K), a compressive strength of 100-200 kPa, and an optimum water vapor diffusion resistance factor which is analogous with a waterproof structure.

## PRODUCT CONTENT

Components	Amount, %
Polystyrene	80-90
Blowing Agents	<12
Flame Retardent	<1
Nucleating Agents	<1
Additives	<1



# Why do I need insulation?

The cheapest energy is the one that is unexpended. Apart from energy efficiency, there are also additional benefits of insulation construction, which are determined below.

- Insulation prevents fuel consumption, therefore decreases waste-gas emissions, which cause global warming and environmental pollution.
- Insulation provides concrete resistivity by averting concrete corrosion. Thus, it increases the durability and the safety of the building against earthquakes.
- Insulation saves %60 of the expenditure on heating & cooling the building. It assists better quality of heating during winter, and better quality of cooling during summer.
- Insulation assists on avoiding the formation of mould growth, black spots and whitcomb in houses by preventing condensation.
- Insulation raises the life standard by balancing the temperature of the building. Thus, it provides a snug and healthy environment in our life time ritual.
- Insulation plays crucial role in country's economy by decreasing energy dependency on other countries.

# LCA Information

<b>Functional Unit</b>	1 R (m <sup>2</sup> K/W) ODE ISIPAN STD XPS Insulation Materials
<b>Time Representativeness</b>	2020
<b>Database(s) and LCA Software Used</b>	Ecoinvent 3.6, SimaPro 9.1

X	A1	Raw Material Supply	Product Stage
X	A2	Transport	
X	A3	Manufacturing	
X	A4	Transport	Construction Process Stage
X	A5	Construction Installation	
ND	B1	Use	Use Stage
ND	B2	Maintenance	
ND	B3	Repair	
ND	B4	Replacement	
ND	B5	Refurbishment	
ND	B6	Operational Energy Use	
ND	B7	Operational Water Use	
X	C1	Deconstruction, demolition	End of Life Stage
X	C2	Transport	
X	C3	Waste Processing	
X	C4	Disposal	
X	D	Future reuse, recycling or energy recovery potentials	Benefits and Loads


X = Included in LCA, ND = Not Declared

The EPD evaluates the environmental impacts of 1 m<sup>2</sup>K/W ODE ISIPAN XPS STD products and during the modeling, all values are taken into account for this unit.

The inventory for the LCA study is based on the 2020 production figures for ISIPAN XPS STD by ODE.

The system boundaries in tabular form for all modules are shown in the table left. This EPD's system boundary is cradle to grave. The system boundary covers A1 - A3 Product Stages, A4-A5 Construction Process Stage and C1-C4 End of Life Stage.

# System Boundary



## A1: Raw Material Supply

ODE Membrane products production starts with raw materials, mainly locally sourced but some transported from other parts of the world. Environmental impacts during the production of all raw materials are reflected in this EPD.

## A2: Transport to Factory

Transport is relevant for delivery of raw materials to the plant and internal transport within the manufacturing plant for each product.

## A3 : Manufacturing

Manufacture of XPS products starts with raw material preparation and continues with extrusion process. Natural gas is the main source of energy in production of Isipan

Insulation materials. Consumed natural gas and electricity is taken into account during the modelling the manufacturing stage of the product.

## A4 : Transport to Site

Manufactured products are sent to customers in different parts of the world. 200 km of road transport and 2000 km (1243 miles) of sea transport are assumed for transportation to clients or to the construction site.

## A5 : Installation

XPS products are applied to the surface by an adhesive material. For installation of XPS products, 4 kg/m<sup>2</sup> adhesive mortar using is assumed.



**C1 : Demolition**

It is assumed that there is no energy use during uninstalation process. This stage is usually done by manpower.

**C2 : Waste Transport**

Average distance from demolition site to final destination is assumed as 100 km.

**C3 : Waste Processing**

There is no need for any waste process.

**C4 : Disposal**


For XPS products, relevant disposal scenarios

are modelled by taking into consideration the fate of the construction and packaging wastes. All construction products disposed into a landfill, which is modelled as such in this LCA. Packaging waste is assumed to end up at packaging recycling.

**D : Benefits & Loads**

There is no potential benefit as the products go completely to the landfill at the end of life. Only the benefit from packaging recycling is taken into account in this LCA model.

# Insulates the Future



# More Information

## **Allocations**

There are no co-products in the production of ODE. Hence, there is no need for co-product allocation. Transport is allocated according to tonnages for almost all raw materials bought by ODE. For the manufacturing of product, no allocation for energy consumption or water consumption was made as the product specific data was available.

Water consumption, energy consumption and raw material transportation were weighted according to 2020 production figures.

In addition, hazardous and non-hazardous waste amounts were also allocated from the 2020 total waste generation.

## **Cut-Off Criteria**

1% cut-off rule is applied to raw materials less than 1% in the composition but making sure their total is below this threshold.

## **REACH Regulation**

No substances included in the Candidate List of Substances of Very High Concern for authorization under the REACH regulations are present in this product either above the threshold for registration with the European Chemicals Agency or above 0.1 % (wt/wt).

## **LCA Modelling, Calculation and Data Quality**

The results of the LCA with the indicators as per EPD requirement are given in the LCA result tables. All energy calculations were obtained using Cumulative Energy Demand (LHV) methodology, while fresh water use is calculated with selected inventory flows in SimaPro according to the PCR.

The SimaPro 9.1 LCA software and the Ecoinvent 3.6 LCA database were used to calculate the environmental impacts. Ecoinvent database were used as generic background data source.

The regional energy datasets were used for all energy calculations.

## **Geographical Scope**

The geographical scope of this EPD is global.

## **Comperability**

A comparison or an evaluation of EPD data is only possible where EN 15804 has been followed, and the same building context and product-specific characteristics of performance are taken into account and the same stages have been included in the system boundary. According to EN 15804, EPD of construction products may not be comperable if they do not comply with the standards.



**LCA**

**Results**

Environmental Impacts for 1 m <sup>3</sup> KW ODE ISIPAN XPS STD Insulation Materials									
Impact Category	Unit	A1-A2-A3	A4	A5	C1	C2	C3	C4	D
GWP - Fossil	kg CO <sub>2</sub> eq	3.41	0.052	5.58	0	0.014	0	0.052	-0.015
GWP - Biogenic	kg CO <sub>2</sub> eq	0.022	9.11E-6	0.031	0	5.54E-6	0	0.771	372E-6
GWP - Luluc	kg CO <sub>2</sub> eq	0.009	23.7E-6	0.004	0	5.18E-6	0	15.5E-6	-11.6E-6
GWP - Total	kg CO <sub>2</sub> eq	3.44	0.052	5.62	0	0.014	0	0.823	-0.015
ODP	kg CFC-11 eq	0.000	11.0E-9	537E-9	0	3.13E-9	0	3.10E-9	-486E-12
AP	mol H+ eq	0.014	0.001	0.036	0	59.9E-6	0	154E-6	-65.9E-6
EP - Freshwater	kg P eq	0.001	3.64E-6	0.002	0	1.21E-6	0	14.1E-6	-4.52E-6
*EP - Freshwater	kg PO <sub>4</sub> eq	0.002	11.1E-6	0.006	0	3.70E-6	0	43.2E-6	-13.8E-6
EP - Marine	kg N eq	0.002	169E-6	0.006	0	17.6E-6	0	0.002	-12.9E-6
EP - Terrestrial	mol N eq	0.024	0.002	0.063	0	192E-6	0	420E-6	-133E-6
POCP	kg NMVOC	0.009	0.001	0.021	0	58.6E-6	0	302E-6	-60.4E-6
ADPE	kg Sb eq	10.6E-6	0.000	0.001	0	379E-9	0	128E-9	-144E-9
ADPF	MJ	68.8	0.731	78.9	0	0.212	0	0.293	-0.423
WDP	m <sup>3</sup> depriv.	1.93	0.002	2.99	0	0.001	0	0.010	-0.012
PM	disease inc.	0.000	3.0E-9	315E-9	0	995E-12	0	1.81E-9	-517E-12
IR	kBq U-235 eq	0.040	0.003	0.344	0	0.001	0	0.002	-0.001
ETP - FW	CTUe	11.8	0.596	179	0	0.187	0	4.41	-0.180
HTTP - C	CTUh	623E-12	20.9E-12	6.70E-9	0	4.81E-12	0	4.39	-4.49E-12
HTTP - NC	CTUh	9.63	573E-12	159E-9	0	188E-12	0	2.37	-124E-12
SQP	Pt	2.25	0.386	30.5	0	0.143	0	0.525	-0.067
Acronyms	GWP-total: Climate change, GWP-fossil: Climate change- fossil, GWP-biogenic: Climate change - biogenic, GWP-luluc: Climate change - land use and transformation, ODP: Ozone layer depletion, AP: Acidification terrestrial and freshwater, EP-freshwater: Eutrophication freshwater, EP-marine: Eutrophication marine, EP-terrestrial: Eutrophication terrestrial, POCP: Photochemical oxidation, ADPE: Abiotic depletion - elements, ADPF: Abiotic depletion - fossil resources, WDP: Water scarcity, PM: Respiratory inorganics - particulate matter, IR: Ionising radiation, ETP-FW: Ecotoxicity freshwater, HTP-c: Cancer human health effects, HTP-nc: Non-cancer human health effects, SQP: Land use related impacts, soil quality.								
Legend	A1: Raw Material Supply, A2: Transport, A3: Manufacturing, A1-A2-A3: Sum of A1, A2 and A3, A4: Transport to Site, A5: Installation, C1: Demolition, C2: Waste Transport, C3: Waste Processing, C4: Disposal, D: Benefits and Loads.								

\*This indicator has been calculated as "kg P eq" as required in the characterization model. (EUTREND model, Struijs et al, 2009b, as implemented in ReCiPe, <http://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml>)



Resource Use for 1 m <sup>2</sup> KW ODE ISIPAN XPS STD Insulation Materials									
Impact Category	Unit	A1-A2-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	1.54	0.007	4.90	0	0.002	0	0.013	-0.019
PERM	MJ	0	0	0	0	0	0	0	0
PERT	MJ	1.54	0.007	4.90	0	0.002	0	0.013	-0.019
PENRE	MJ	68.8	0.731	78.9	0	0.212	0	0.293	-0.423
PENRM	MJ	0	0	0	0	0	0	0	0
PENRT	MJ	68.8	0.731	78.9	0	0.212	0	0.293	-0.423
SM	kg	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m <sup>3</sup>	0.010	110E-6	0.073	0	36.7E-6	0	269E-6	-54.0E-6
Waste & Output Flows for 1 m <sup>2</sup> KW ODE ISIPAN XPS STD Insulation Materials									
Impact Category	Unit	A1-A2-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	383E-9	0	0	0	0	0	0	0
NHWD	kg	22.2E-6	0	0	0	0	0	0	0
RWD	MJ	0	0	0	0	0	0	0	0
CRU	MJ	0	0	0	0	0	0	0	0
MFR	MJ	0	0	0	0	0	0	0	0
MER	MJ	0	0	0	0	0	0	0	0
EE (Electrical)	kg	0	0	0	0	0	0	0	0
EE (Thermal)	MJ	0	0	0	0	0	0	0	0
Acronyms	PERE: Use of renewable primary energy excluding resources used as raw materials, PERM: Use of renewable primary energy resources used as raw materials, PERT: Total use of renewable primary energy, PENRE: Use of non-renewable primary energy excluding resources used as raw materials, PENRM: Use of non-renewable primary energy resources used as raw materials, PENRT: Total use of non-renewable primary energy, SM: Secondary material, RSF: Renewable secondary fuels, NRSF: Non-renewable secondary fuels, FW: Net use of fresh water, HWD: Hazardous waste disposed, NHWD: Non-hazardous waste disposed, RWD: Radioactive waste disposed, CRU: Components for reuse, MFR: Material for recycling, MER: Materials for energy recovery, EE (Electrical): Exported energy electrical, EE (Thermal): Exported energy Thermal.								
Legend	A1: Raw Material Supply, A2: Transport, A3: Manufacturing, A1-A2-A3: Sum of A1, A2 and A3, A4: Transport to Site, A5: Installation, C1: Demolition, C2: Waste Transport, C3: Waste Processing, C4: Disposal, D: Benefits and Loads.								

# References



/GPI/ General Programme Instructions of the International EPD® System. Version 4.0

/ISO 9001/ Quality management systems – Requirements

/ISO 14001/ Environment Management System- Requirements

/EN 15804:2012+A2:2019/ Sustainability of construction works - Environmental Product Declarations — Core rules for the product category of construction products

/ISO 14020:2000/ Environmental labels and declarations — General principles

/ISO 14025/ ISO 14025:2006 Preview Environmental labels and declarations -- Type III environmental declarations -- Principles and procedures

/ISO 14040-44/ ISO 14040:2006-10, Environmental management - Life cycle assessment -Principles and framework (ISO 14040:2006) and Requirements and guidelines (ISO 14044:2006)

/ISO 27001/ ISO 27001-2013 Information Security Management System - Requirements

/ISO 45001/ Health and Safety Management System - Requirements






/ISO 50001/ Energy Management Certificate - Requirements

/PCR for Construction Products and CPC 54 Construction Services/ Prepared by IVL  
IVL Swedish Environmental Research Institute Secretariat of the International EPD® System, 2019:14 Version 1.11, DATE 2021-02-05

/Ecoinvent/ Ecoinvent Centre, [www.ecoinvent.org](http://www.ecoinvent.org)

/SimaPro/ SimaPro LCA Package, Pré Consultants, the Netherlands, [www.pre-sustainability.com](http://www.pre-sustainability.com)

# Contact Informations

Programme	<p>EPD registered through fully aligned regional programme: EPD Turkey: <a href="http://www.epdturkey.org">www.epdturkey.org</a></p>	<p>The International EPD® System <a href="http://www.environdec.com">www.environdec.com</a></p>
	 <p>ENVIRONMENTAL PRODUCT DECLARATIONS</p>	 <p>THE INTERNATIONAL EPD® SYSTEM</p>
Programme operator	<p>EPD Turkey: SÜRATAM – Turkish Centre for Sustainable Production Research &amp; Design Nef 09 B Blok No:7/15, 34415 Kagithane / Istanbul, TURKEY</p> <p><a href="http://www.epdturkey.org">www.epdturkey.org</a> <a href="mailto:info@epdturkey.org">info@epdturkey.org</a></p>	<p>EPD International AB Box 210 60 SE-100 31 Stockholm, Sweden</p> <p><a href="http://www.environdec.com">www.environdec.com</a> <a href="mailto:info@environdec.com">info@environdec.com</a></p>
Owner of the declaration	 <p>INSULATES THE FUTURE</p> <p>ODE Industry and Trade Inc. Piyale Paşa Bulvarı Ortadoğu Plaza K.12 34384 Okmeydanı</p> <p>Şişli / İstanbul/Turkey</p>	<p>Contact: Derya Gürbüz Ilgaz Quality Manager Phone: +90 212 210 49 06</p> <p><a href="http://www.ode.com.tr">www.ode.com.tr</a> <a href="mailto:ode@ode.com.tr">ode@ode.com.tr</a></p>
LCA practitioner & EPD Design	 <p>Sustainability Consulting</p> <p>Turkey: Lalegül Sok. No:7/18 Kagithane 34415 4. Levent – Istanbul, Turkey +90 212 281 13 33</p>	<p>United Kingdom: 4 Clear Water Place Oxford OX2 7NL, UK 0 800 722 0185</p> <p><a href="http://www.metsims.com">www.metsims.com</a> <a href="mailto:info@metsims.com">info@metsims.com</a></p>
3rd party verifier		<p>Professor Vladimír Kocí LCA Studio Šárecká 5,16000 Prague 6 - Czech Republic <a href="http://www.lcastudio.cz">www.lcastudio.cz</a></p>



**INSULATES THE FUTURE**

[www.ode.com.tr](http://www.ode.com.tr)